Predicting the contents of an IP header

This is an example of how to format your results for Lab 2. Here, we predict and observe the IP header of a TCP/IP packet. In the lab, you will predict the UDP header and payload of a UDP packet (ignoring the IP header).

Predicted Contents

| Field name and contents in decimal | Field contents in hexadecimal |
|--|---|
| Version: 4 bits (0.5 byte): 4 | 0x4 (0b0100) |
| Header length: 4 bits (0.5 byte): 20 | 0x14? 0x4? 0x0? (How to fit in just 0.5 bytes?) |
| Type of service: 8 bits (1 byte): unknown | <mark>0x</mark> |
| Datagram Length: 16 bits (2 bytes): 20 bytes (IP header) + 20 bytes (TCP | <mark>0x00 28</mark> |
| header) + 0 bytes (TCP data) = 40. (The first TCP message sent contains no data because it is part of a 3-way handshake to set up the connection.) | |
| 16-bit identifier, flags, and 13-bit fragmentation offset: 32 bits (8 bytes): unknown | 0x |
| Time-to-live: 8 bits (1 byte): 255? | 0xff? |
| Protocol: 8 bits (1 byte): TCP (6) | <mark>0x06</mark> |
| Header checksum: 16 bits (2 bytes): unknown | <mark>0x</mark> |
| Source IP address: 32 bits (4 bytes): 192.168.1.15 | <mark>0xc0 a8 01 0f</mark> |
| Destination IP address: 32 bits (4 bytes): 98.142.108.75 | 0x62 8e ac 2b |
| Options: 0 bits: none | |
| Data: 160 bits (20 bytes): TCP header | (not included in this example – do include the payload in your lab) |

Complete Predicted Packet

Prediction: 40 -- 00 28 -- -- -- -- -- ff 06 -- c0 a8 01 0f 62 8e ac 2b

Complete Actual Packet

Actual: 45 00 00 34 47 ca 40 00 80 06 22 69 c0 a8 01 0f 62 8e 6c 4b

Actual Contents

| Field name and contents in decimal | Field contents in hexadecimal |
|---|--------------------------------|
| Version: 4 bits (0.5 byte): 4 (same as predicted) | <mark>0x4</mark> |
| Header length: 4 bits (0.5 byte): 5 * (32-bit words) = 5*4 bytes = 20 bytes | 0x5 |
| Type of service: 8 bits (1 byte): 0 | 0x00 |
| Datagram Length: 16 bits (2 bytes): 52 = 20 bytes (IP header) + 32 bytes | 0x00 34 |
| (TCP header) + 0 bytes data. The TCP header was longer than expected | |
| because it contained 12 bytes in the "options" field, to set the Maximum | |
| Segment Size (MSS), Window Scale, and SACK Permitted. | |
| 16-bit identifier, flags, and 13-bit fragmentation offset: 32 bits (4 bytes): I | 0x47 ca 40 00 |
| computed the byte size wrong. 32/8 = 4, not 8! | |
| Time-to-live: 8 bits (1 byte): 128 (about half what I predicted) | <mark>0x80</mark> |
| Protocol: 8 bits (1 byte): TCP (6) (same as predicted) | 0x06 |
| Header checksum: 16 bits (2 bytes): 0x2269 (I only included | 0x22 69 |
| one blank byte instead of two) | |
| Source IP: 32 bits (4 bytes): 192.168.1.15 (same as predicted) | <mark>0xc0 a8 01 0f</mark> |
| Destination IP: 32 bits (4 bytes): 98.142.108.75 (error converting to hex) | 0x62 8e 6c 4b |
| Options: 0 bits: None | |
| Data: 256 bits (32 bytes): TCP header (see above) | (not included in this example) |